HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	1/1
Document No.	DC110-000580	Revision	1.2

TO   :

Date   :   Jan., 08, 2009

HannStar Product Specification
(Preliminary)

Model: **HSD121PHW1 -A01**

Note: (1) The information contained herein is tentative and may be changed without prior notices

(2) Please contact HannStar Display Corp. before designing your product based on this module specification.

(3) The information contained herein is presented merely to indicate the characteristics and performance of our products. No responsibility is assumed by HannStar for any intellectual property claims or other problems that may result from application based on the module described herein.

(4) The mark " ** " of Model means sub-model code.

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	2/2
Document No.	DC110-000580	Revision	1.2

Record of Revisions

Rev.	Date	Sub-Model	Description of change
1.2	Jan, 08, 2009	A01	Preliminary Product Information was first released.

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	3/3
Document No.	DC110-000580	Revision	1.2

Contents

HannStar HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	4/4
Document No.	DC110-000580	Revision	1.2

1.0 GENERAL DESCRIPTION

1.1 Introduction

HannStar Display model HSD121PHW1-A is a color active matrix thin film transistor (TFT) liquid crystal display (LCD) that uses amorphous silicon TFT as a switching device. This model is composed of a TFT LCD panel, a driving circuit and a back light system. This TFT LCD has a 16 (16:9) inch diagonally measured active display area with HD (1366 horizontal by 768 vertical pixel) resolution.

1.2 Features

- 12.1 (16:9 diagonal) inch configuration
- One channel LVDS interface
- 262K color by 6 bit R.G.B signal input
- RoHS Compliance
- Halogen Free

1.3 Applications

- NB

1.4 General information

Item		Specification	Unit
Outline Dimension		279 x 167.2 x 4.8 (Typ.)	mm
Display area		268.01(H) x 150.68(V)	mm
Number of Pixel		1366 RGB (H) x 768(V)	pixels
Pixel pitch		0.1962(H) x 0.1962(V)	mm
Pixel arrangement		RGB Vertical stripe	
Display mode		Normally white	
NTSC		50	%
Surface treatment		Glare, Hard-Coating (3H)	
Weight		(250) (Typ.)	g
Back-light		White LED	
Power Consumption	Logic System	(0.85W) (Max.)	W
	B/L System	(2.4W) (Max.)	W

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	5/5
Document No.	DC110-000580	Revision	1.2

1.5 Mechanical Information

Item		Min.	Typ.	Max.	Unit
Module Size	Horizontal (H)	278.5	279	279.5	mm
	Vertical (V)	166.7	167.2	167.7	mm
	Depth (D)	—	(4.8)	(5.1)	mm
Weight		—	(250)	(265)	g

2.0 ABSOLUTE MAXIMUM RATINGS

2.1 Electrical Absolute Rating

2.1.1 TFT LCD Module

Item	Symbol	Min.	Max.	Unit	Note
Logic Supply voltage	V_{DD}	-0.3	6.0	V	

2.1.2 Environment Absolute Rating

Item	Symbol	Min.	Max.	Unit	Note
Operating Temperature	T_{opa}	0	50	℃	
Storage Temperature	T_{stg}	-20	60	℃	

HannStar HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	6/6
Document No.	DC110-000580	Revision	1.2

3.0 OPTICAL CHARACTERISTICS

3.1 Optical specification

Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Contrast		CR		―	(500)	―		(1)(2)(4)
Response time		RT		―	(12)	―	msec	(1)(3)
White luminance (5 point)		Y_L		―	(200)	―	cd/m^2	(1)(4)(5) (I_L=20mA)
Color chromaticity (CIE1931)	Red	R_x	$\ominus$=0 Normal viewing angle	―	(TBD)	―		
		R_Y		―	(TBD)	―		
	Green	G_x		―	(TBD)	―		
		G_Y		―	(TBD)	―		
	Blue	B_x		―	(TBD)	―		
		B_Y		―	(TBD)	―		
	White	W_x		0.283	0.313	0.343		
		W_y		0.299	0.329	0.359		
Viewing angle	Hor.	$\ominus_L$	CR>10	―	45	―		(1)(4)
		$\ominus_R$		―	45	―		
	Ver.	$\ominus_U$		―	15	―		
		$\ominus_D$		―	35	―		
Brightness uniformity		B_{UNI}	$\ominus$=0 (5point)	80	―	―	%	(6)
Brightness Uniformity		B_{UNI}	$\ominus$=0 (13 points)	70	―	―	%	(6)

3.2 Measuring Condition

■ Measuring surrounding：dark room

■ Ambient temperature：25±2^{o}C

■ 15min. warm-up time.

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	7/7
Document No.	DC110-000580	Revision	1.2

3.3 Measuring Equipment

■ FPM520 of Westar Display technologies, INC., which utilized SR-3 for Chromaticity and BM-5A for other optical characteristics.

■ Measuring spot size：20 ~ 21 mm

**Note (1)** Definition of Viewing Angle:

Note (2) Definition of Contrast Ratio (CR) :

measured at the center point of panel

$$CR = \frac{\text{Luminance with all pixels white}}{\text{Luminance with all pixels black}}$$

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	8/8
Document No.	DC110-000580	Revision	1.2

Note (3) Definition of Response Time : Sum of T_R and T_F

white(TFT OFF)   black   (TFT ON)   white(TFT OFF)

T_R T_F

Optical response

100%
90%

10%
0%

time

Note (4) Definition of optical measurement setup

LCD Panel

Field = 1°

Photo-detector (BM-5A)

120cm

The information contained in this document is the exclusive property of HannStar Display Corporation. It shall not be disclosed, distributed or reproduced in whole or in part without written permission of HannStar Display Corporation.

HannStar　Display　Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	9/9
Document No.	DC110-000580	Revision	1.2

Note (5) Definition of Average Luminance Uniformity of White (5 Point)

$$\text{Average Luminance Uniformity} = \frac{Y_1+Y_2+Y_3+Y_4+Y_5}{5}$$

Note (6) Definition of brightness uniformity

$$\text{Luminance uniformity(5 points)} = \frac{\text{(Min Luminance of 5 points)}}{\text{(Max Luminance of 5 points)}} \times 100\%$$

$$\text{Luminance uniformity(13points)} = \frac{\text{(Min Luminance of 13 points)}}{\text{(Max Luminance of 13 points)}} \times 100\%$$

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	10/10
Document No.	DC110-000580	Revision	1.2

4.0 BLOCK DIAGRAM
4.1 TFT LCD Module:

4.2 Pixel Format

LCD Display Area

1 Pixel

R G B R

768 Lines

1366 pixel (4098 Dots)

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	11/11
Document No.	DC110-000580	Revision	1.2

4.3 Relationship Between Displayed Color and Input

	Display	MSB R5	R4	R3	R2	R1	LSB R0	MSB G5	G4	G3	G2	G1	LSB G0	MSB B5	B4	B3	B2	B1	LSB B0	Gray scale level
Basic color	Black	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	-
	Blue	L	L	L	L	L	L	L	L	L	L	L	L	H	H	H	H	H	H	-
	Green	L	L	L	L	L	L	H	H	H	H	H	H	L	L	L	L	L	L	-
	Light Blue	L	L	L	L	L	L	H	H	H	H	H	H	H	H	H	H	H	H	-
	Red	H	H	H	H	H	H	L	L	L	L	L	L	L	L	L	L	L	L	-
	Purple	H	H	H	H	H	H	L	L	L	L	L	L	H	H	H	H	H	H	-
	Yellow	H	H	H	H	H	H	H	H	H	H	H	H	L	L	L	L	L	L	-
	White	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	-
Gray scale of Red	Black	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L0
	Dark ↑↓ Light	L	L	L	L	L	H	L	L	L	L	L	L	L	L	L	L	L	L	L1
		L	L	L	L	H	L	L	L	L	L	L	L	L	L	L	L	L	L	L2
		⋮						⋮						⋮						L3…L60
		H	H	H	H	L	H	L	L	L	L	L	L	L	L	L	L	L	L	L61
		H	H	H	H	H	L	L	L	L	L	L	L	L	L	L	L	L	L	L62
	Red	H	H	H	H	H	H	L	L	L	L	L	L	L	L	L	L	L	L	Red L63
Gray scale of Green	Black	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L0
	Dark ↑↓ Light	L	L	L	L	L	L	L	L	L	L	L	H	L	L	L	L	L	L	L1
		L	L	L	L	L	L	L	L	L	L	H	L	L	L	L	L	L	L	L2
		⋮						⋮						⋮						L3…L60
		L	L	L	L	L	L	H	H	H	H	L	H	L	L	L	L	L	L	L61
		L	L	L	L	L	L	H	H	H	H	H	L	L	L	L	L	L	L	L62
	Green	L	L	L	L	L	L	H	H	H	H	H	H	L	L	L	L	L	L	Green L63
Gray scale of Blue	Black	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L0
	Dark ↑↓ Light	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	H	L1
		L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	H	L	L2
		⋮						⋮						⋮						L3…L60
		L	L	L	L	L	L	L	L	L	L	L	L	H	H	H	H	L	H	L61
		L	L	L	L	L	L	L	L	L	L	L	L	H	H	H	H	H	L	L62
	Blue	L	L	L	L	L	L	L	L	L	L	L	L	H	H	H	H	H	H	Blue L63
Gray scale of White & Black	Black	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L0
	Dark ↑↓ Light	L	L	L	L	L	H	L	L	L	L	L	H	L	L	L	L	L	H	L1
		L	L	L	L	H	L	L	L	L	L	H	L	L	L	L	L	H	L	L2
		⋮						⋮						⋮						L3…L60
		H	H	H	H	L	H	H	H	H	H	L	H	H	H	H	H	L	H	L61
		H	H	H	H	H	L	H	H	H	H	H	L	H	H	H	H	H	L	L62
	White	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	White L63

The information contained in this document is the exclusive property of HannStar Display Corporation. It shall not be disclosed, distributed or reproduced in whole or in part without written permission of HannStar Display Corporation.

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	12/12
Document No.	DC110-000580	Revision	1.2

5.0 INTERFACE PIN CONNECTION

TFT LCD Module： **CN1** (Input signal):): FI-XB30SL-HF10 (JAE or equivalent)

Pin No.	Signal	Description
1	GND	Ground
2	VDD	3.3V Power
3	VDD	3.3V Power
4	V_EDID	3.3V Power for EDID
5	PWM	System PWM Signal Input
6	CLK_EDID	EDID Clock Input
7	DATA_EDID	EDID Data Input
8	RXIN0-	LVDS Signal - channel0-
9	RXIN0+	LVDS Signal+ channel0+
10	GND	Ground
11	RXIN1-	Data Input channel1-
12	RXIN1+	Data Input channel1+
13	GND	Ground
14	RXIN2-	Data Input channel2-
15	RXIN2+	Data Input channel2+
16	GND	Ground
17	RXCLKIN-	Data Input CLK-
18	RXCLKIN+	Data Input CLK+
19	GND	Ground
20	NC	NC
21	NC	NC
22	GND	Ground
23	GND	Ground
24	VLED	LED Input voltage 7V~21V
25	VLED	LED Input voltage 7V~21V
26	VLED	LED Input voltage 7V~21V
27	LED_EN	LED Enable Signal
28	NC	NC
29	NC	NC
30	NC	NC

Note：The brightness of LCD panel could be changed by adjusting PWM

HannStar　HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	13/13
Document No.	DC110-000580	Revision	1.2

6.0　ELECTRICAL CHARACTERISTICS
6.1　TFT LCD Module

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Supply Voltage	V_{DD}	3.0	3.3	3.6	V	**Note (2)**
Current of power supply	IDD	-	0.3	-	A	V_{DD} =3.3V、L0 pattern
Inrush current	I_{RUSH}	-	-	1.50	A	Note (2)

Note (1): V_{DD} dip condition:

When VDD operating within 2.7V≦VDD<3.0V，td≦10ms , the display may momentarily become abnormal.

VDD<2.7V , VDD dip condition should also follow the Power On/Off conditions for supply voltage.

.

VDD

2.7v　3.0v

GND

td

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	14/14
Document No.	DC110-000580	Revision	1.2

Note ：**(2)** Power on Inrush current test circuit

V_{in} rising time

The information contained in this document is the exclusive property of HannStar Display Corporation. It shall not be disclosed, distributed or reproduced in whole or in part without written permission of HannStar Display Corporation.

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	15/15
Document No.	DC110-000580	Revision	1.2

6.2 Switching Characteristics for LVDS Receiver

Item	Symbol	Min.	Typ.	Max.	Unit	Conditions
Differential Input High Threshold	V_{th}	—	—	100	mV	V_{CM}=1.2V
Differential Input Low Threshold	V_{tl}	-100	—	—	mV	
Input Current	I_{IN}	-10	—	+10	uA	
Differential input Voltage	$|V_{ID}|$	0.1	—	0.6	V	
Common Mode Voltage Offset	V_{CM}	$(|V_{ID}|/2)$	1.25	$1.8-0.4-(|V_{ID}|/2)$	V	

6.3 Bit Mapping & Interface Definition

LVDS Receiver Input Timing Definition
for 6bits LVDS input

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	16/16
Document No.	DC110-000580	Revision	1.2

6.4 Interface Timing (DE mode)

Item	Symbol	Min.	Typ.	Max.	Unit
Frame Rate	--	(55)	(60)	(TBD)	Hz
Frame Period	t1	(778)	(806)	(888)	line
Vertical Display Time	t2	(768)	(768)	(768)	line
Vertical Blanking Time	t3	(10)	(38)	(120)	line
1 Line Scanning Time	t4	(1437)	(1560)	(1936)	clock
Horizontal Display Time	t5	(1366)	(1366)	(1366)	clock
Horizontal Blanking Time	t6	(71)	(194)	(570)	clock
Clock Rate	t7	(50.3)	(75.44)	(80)	MHz

Timing Diagram of Interface Signal (DE mode)

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	17/17
Document No.	DC110-000580	Revision	1.2

6.5 Power On / Off Sequence

Item	Min.	Typ.	Max.	Unit	Remark
TP1	0.5	--	10	msec	
TP2	0	--	50	msec	
TP3	0	--	50	msec	
TP4	1000	--	--	msec	
TP5	200	--	--	msec	
TP6	200	--	--	msec	
TP7	0.5	--	10	msec	

Note：(1) The supply voltage of the external system for the module input should be the same as the definition of V_{DD}.

(2) Apply the lamp volatge within the LCD operation range. When the back-light turns on before the LCD operation or the LCD truns off before the back-light turns off, the display may momentarily become white.

(3) In case of VDD = off level, please keep the level of input signal on the low or keep a high impedance.

(4) TP4 should be measured after the module has been fully discharged between power off and on period.

(5) Interface signal shall not be kept at high impedance when the power is on.

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	18/18
Document No.	DC110-000580	Revision	1.2

6.6 Backlight Unit

Parameter	Symbol	Min	Typ	Max	Units	Condition
LED Current	I_F	--	(20)	(20.6)	mA	Ta=25℃
LED Voltage	V_F	(3.0)	(3.2)	(3.4)	Volt	Ta=25℃
LED Power consumption	P_{LED}	--	TBD	TBD	Watt	Ta=25℃ Note (1)
LED Life-Time	N/A	10,000	--	--	Hour	Ta=25℃ $I_{F=}$20mA Note (2)

Note (1): Calculator value for reference $P=I_F$ x V_F x N (LED Qty')

Note (2): The LED lifetime defines as the estimated time to 50% degradation of final luminous.

6.7 LED Driver

6.7.1　Absolute Maximum Ratings

Item	Symbol	Min.	Max.	Unit	Note
LED Power Supply voltage	V_{LED}	-0.3	24	Volt	
LED_EN, PWM pin Voltage	V_{EN}, V_{PWM}	--	5.5	Volt	

6.7.2　DC Electrical Characteristics

| Parameter	Symbol	Min	Typ	Max	Units	Remark
LED Power Supply Voltage	V_{LED}	7.0	--	21.0	Volt	
LED_EN High Threshold	V_{ENH}	2.0	--	--	Volt	
LED_EN Low Threshold	V_{ENL}	--	--	0.3	Volt	
PWM High Threshold	V_{PWMH}	3.0	--	--	Volt	
PWM Low Threshold	V_{PWML}	--	--	0.2	Volt	
PWM Frequency	F_{PWM}	(225)	--	(275)	Hz	
PWM Duty Cycle	T_D	(10)	--	(100)	%	Note(1)

HannStar Display Corp.

| Document Title | HSD121PHW1-A01 Preliminary Specification | Page No. | 19/19 |
| Document No. | DC110-000580 | Revision | 1.2 |

Note (1): PWM Duty Cycle

Duty Cycle = (t / T) *100%

6.7.3 LED Power on/off sequence

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	20/20
Document No.	DC110-000580	Revision	1.2

Symbol	Value			Unit
	Min	Typ	Max	
T1	10	--	--	ms
T2	10	--	--	
T3	50	--	--	
T4	0	--	--	
T5	10	--	--	

Note (1): The duty of LED dimming signal should be more than 20% in T2 and T3
Note (2): PWM can adjust brightness to control Pin. Pulse duty the bigger the brighter

HannStar Display Corp.

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	21/21
Document No.	DC110-000580	Revision	1.2

7.0 Reliability test items

No.	Item	Conditions	Remark
1	High Temperature Storage	Ta=+60^{o}C, 240hrs	
2	Low Temperature Storage	Ta=-20^{o}C, 240hrs	
3	High Temperature Operation	Ta=+50^{o}C, 500hrs	
4	Low Temperature Operation	Ta=0^{o}C, 500hrs	
5	Thermal Cycling Test (non operation)	-20^{o}C(30min)→+60^{o}C(30min),100 cycles	
6	Vibration	Sine Wave 1.5G, 5~500Hz, XYZ 30min/each direction	
7	Shock	Half-Sine, 200G, 2ms, ±XYZ, 1time	

Storage / Operating temperature

Humidity (%)

Operating Range

Storage Range

Temperature (^{o}C)

Note . Max wet bulb temp.=39^{o}C

The information contained in this document is the exclusive property of HannStar Display Corporation. It shall not be disclosed, distributed or reproduced in whole or in part without written permission of HannStar Display Corporation.

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	22/22
Document No.	DC110-000580	Revision	1.2

8.0   OUTLINE DIMENSION

Unit : mm

8.1   Front View Outline Dimension

The information contained in this document is the exclusive property of HannStar Display Corporation. It shall not be disclosed, distributed or reproduced in whole or in part without written permission of HannStar Display Corporation.

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	23/23
Document No.	DC110-000580	Revision	1.2

8.2 Back View Outline Dimension

HannStar HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	24/24
Document No.	DC110-000580	Revision	1.2

9.0　LOT MARK

9.1　Lot Mark

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15

Code 1,2,3,4,5,6: HannStar internal flow control code.

Code 7: production location.

Code 8: production year.

Code 9: production month.

Code 10,11,12,13,14,15: serial number.

Note (1) Production Year

Year	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008
Mark	9	0	1	2	3	4	5	6	7	8

Note (2) Production Month

Month	Jan.	Feb.	Mar.	Apr.	May.	Jun.	Jul.	Aug.	Sep.	Oct	Nov.	Dec.
Mark	1	2	3	4	5	6	7	8	9	A	B	C

9.2　Location of Lot Mark

(1) The label is attached to the backside of the LCD module.

(2) This is subject to change without prior notice.

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	25/25
Document No.	DC110-000580	Revision	1.2

10.0 PACKAGE SPECIFICATION

10.1 Packing form

(1) Package quantity in one carton: TBD.

(2) Carton size: TBD.

10.2 Packing assembly drawings

11.0 GENERAL PRECAUTION

11.1 Use Restriction

This product is not authorized for use in life supporting systems, aircraft navigation control systems, military systems and any other application where performance failure could be life-threatening or otherwise catastrophic.

11.2 Disassembling or Modification

Do not disassemble or modify the module. It may damage sensitive parts inside LCD module, and may cause scratches or dust on the display. HannStar does not warrant the module, if customers disassemble or modify the module.

11.3 Breakage of LCD Panel

11.3.1.If LCD panel is broken and liquid crystal spills out, do not ingest or inhale liquid crystal, and do not contact liquid crystal with skin.

11.3.2. If liquid crystal contacts mouth or eyes, rinse out with water immediately.

11.3.3. If liquid crystal contacts skin or cloths, wash it off immediately with alcohol and rinse thoroughly with water.

11.3.4. Handle carefully with chips of glass that may cause injury, when the glass is broken.

11.4 Electric Shock

11.4.1. Disconnect power supply before handling LCD module.

11.4.2. Do not pull or fold the LED cable.

11.4.3. Do not touch the parts inside LCD modules and the fluorescent LED's connector or cables in order to prevent electric shock.

Global LCD Panel Exchange Center   www.panelook.com   屏库:全球液晶屏交易中心

HannStar Display Corp.

Document Title	HSD121PHW1-A01 Preliminary Specification	Page No.	26/26
Document No.	DC110-000580	Revision	1.2

11.5 Absolute Maximum Ratings and Power Protection Circuit

11.5.1. Do not exceed the absolute maximum rating values, such as the supply voltage variation, input voltage variation, variation in parts' parameters, environmental temperature, etc., otherwise LCD module may be damaged.

11.5.2. Please do not leave LCD module in the environment of high humidity and high temperature for a long time.

11.5.3. It's recommended to employ protection circuit for power supply.

11.6 Operation

11.6.1 Do not touch, push or rub the polarizer with anything harder than HB pencil lead.

11.6.2 Use fingerstalls of soft gloves in order to keep clean display quality, when persons handle the LCD module for incoming inspection or assembly.

11.6.3 When the surface is dusty, please wipe gently with absorbent cotton or other soft material.

11.6.4 Wipe off saliva or water drops as soon as possible. If saliva or water drops contact with polarizer for a long time, they may causes deformation or color fading.

11.6.5 When cleaning the adhesives, please use absorbent cotton wetted with a little petroleum benzine or other adequate solvent.

11.7 Mechanism

Please mount LCD module by using mounting holes arranged in four corners tightly.

11.8 Static Electricity

11.8.1 Protection film must remove very slowly from the surface of LCD module to prevent from electrostatic occurrence.

11.8.2 Because LCD module use CMOS-IC on circuit board and TFT-LCD panel, it is very weak to electrostatic discharge. Please be careful with electrostatic discharge. Persons who handle the module should be grounded through adequate methods.

11.9 Strong Light Exposure

The module shall not be exposed under strong light such as direct sunlight. Otherwise, display characteristics may be changed.

11.10 Disposal

When disposing LCD module, obey the local environmental regulations.